

# LOCTITE 55

## A better joint for pipe systems

Modern technology, traditional skills

LOCTITE 55 pipe sealing cord is the fast, easy and secure sealant for threaded pipes. Fast application and an instant seal – it could not be easier. It saves you up to 50% of the time you need with traditional tapes or hemp and paste combinations. Work fast and clean and save yourself time and money.

### A single reel of LOCTITE 55 will seal:

Thread size	1/2	3/4	1
Approx. number of joints – 160 metre pack	405	275	190
Approx. number of joints – 50 metre pack	125	85	60



### How to apply



1. For chrome & stainless steel fittings slightly roughen the thread.

2. Wind the sealing cord onto the first pitches clockwise and cross over the threads. See the pack for the correct number of turns.

3. Cut the cord using the attached cutting device and press the loose end onto the thread.

4. Screw the fittings with a pipe wrench. Only reposition if necessary.

### Benefits in using LOCTITE 55:



Fast, clean and easy to use



Re-adjustment up to 45°



For metal & plastic joints

### Newly designed dispenser

**NEW**

› Mess-free

› Hassle-free cutting with integral blade

› Ergonomic design

› One component & one product does all – gas, water, etc

› Now with more content: **160 m**



**WRAS:**  
Approval for use with potable water up to 85°C (BS 6920)



**BAM:**  
Certificate for ignition sensitivity to gaseous oxygen  
Max. temp.: up to 60°C  
Max. oxygen pressure: up to 20 bar



**DVGW:**  
Approval for gas and water (EN 751-2, Class ARp)  
**KTW:**  
Approval for potable water



**NSF:**  
Certified to NSF / ANSI, Standard 61

